



NEW MONOCRYSTALLINE MODULES



The PWM1700 is Photowatt's 5 inch high efficiency module. Thanks to its optimum size it is easy to handle and specifically dedicated to large scale grid connected applications.

The PWM1700 module uses Photowatt's monocrystalline technology. The solar cells are individually characterized and electronically matched prior to interconnection. Encapsulation is realised between the high transmission tempered glass and the resistant thermal setting Tedlar®. The encapsulant, ethylene vinyl acetate, cushions the solar cells within the laminate and protect the cells from etching. The rear surface of the module is completely sealed from moisture and mechanical damage by a continuous high strength polymer sheet.

With a tolerance improvement to +/- 3%, the PWM1700 modules ensure more power homogeneity in installations, and a financial investment corresponding to the real power produced.

APPLICATIONS

- Grid connected system
- Water pumping
- Telecommunications
- Battery charging system
- Cathodic protection system
- Building integrated power system

- High efficiency modules
- 8x9 5' inch monocrystalline cells (125,50 x 125,50 mm)
- Reinforced anodised aluminium frame
- 12V and UL versions available on request
- **Product warranty : 5 years***
- **Efficiency warranty : 25 years***
- **Power tolerance : +/- 3%**
- **Quality insurance : ESTI (61215), TÜV ** (Safety Class II), ISO 9001...**



PACKING INFORMATION

Module weight	Kg	18
Module size	mm	1237 x 1082 x 38
Packing configuration	modules	2 per cartons
Packing size	mm	1350 x 1130 x 102
Modules packed weight	Kg	39
Maximum pallet size (34 modules)	mm	1360 x 1130 x 1770
Maximum pallet weight	Kg	678

ELECTRICAL CHARACTERISTICS

PWM1700		cells 125 X 125 Ø 165	
Typical power	W	170	180
Minimum power	W	165	175
Voltage at typical power	V	35,2	35,4
Current at typical power	A	4,85	5,1
Short circuit current	A	5,3	5,5
Open circuit voltage	V	44,4	44,6
Maximum system voltage	V	770 DC	
Temperature coefficient		α =+1,46 mA/°C ; β = -158 mV/°C ; γ P/ P = -0,43 % /°C	
Power specifications at 1000 W/m ² : 25°C : AM 1,5			

* According to general warranty conditions

** Pending




PHOTOWATT


Solutions for natural power

33 Rue Saint Honoré – Z.I. Champfleuri
38300 Bourgoin-Jallieu - FRANCE
Phone +33 (0)4 74 93 80 20 - Fax +33 (0)4 74 93 80 40
www.photowatt.com - marketing@photowatt.com

January 2006 - The characteristics of this document are representative of the products and have no contractual value. Subject to products improvements, Photowatt reserves the right to modify the characteristics without prior notification.



CABLES DETAILS




The mounting frame
screw not passing
beyond the frame

The module is protected by 4 bypass diodes (1 bypass diode per 18 cells)

$I=F(V)$ à $E=1 \text{ kW/m}^2$, $AM=1,5$ as a function of the junction temperature

Amperes



$I=F(V)$ à $T = 25^\circ\text{C}$ as a function of this irradiance E (kW / m^2), $AM 1,5$.

Amperes

